

US009614275B2

# (12) United States Patent Cicero

# (10) Patent No.: US 9,614,275 B2 (45) Date of Patent: Apr. 4, 2017

### (54) METHODS AND APPARATUS FOR WIDE BANDWIDTH ANTENNA WITH ENHANCED CONNECTION

## (71) Applicant: **Raytheon Company**, Waltham, MA

### (72) Inventor: Patrick Cicero, Tucson, AZ (US)

## (73) Assignee: **RAYTHEON COMPANY**, Waltham,

MA (US)

### (\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 34 days.

(21) Appl. No.: 14/847,503

(22) Filed: Sep. 8, 2015

### (65) Prior Publication Data

US 2017/0069961 A1 Mar. 9, 2017

# (51) Int. Cl. #01Q 13/10 (2006.01) #01Q 1/38 (2006.01) #01Q 9/04 (2006.01) #01Q 13/02 (2006.01) #01Q 1/28 (2006.01)

### (58) Field of Classification Search

CPC ............ H01Q 13/10; H01Q 13/02; H01Q 1/28 See application file for complete search history.

### (56) References Cited

### U.S. PATENT DOCUMENTS

2,822,542	A	2/1958	Butterfield et al.	
4,803,495	A *	2/1989	Monser	H01Q 1/523
				343/725
5,126,751	A	6/1992	Wada et al.	
6,278,410	B1	8/2001	Soliman et al.	
7,589,686	B2	9/2009	Balzovsky et al.	
7,649,501	B2	1/2010	Wong et al.	
8,736,502	B1*	5/2014	Langfield	H01Q 19/06
			•	343/753
2014/0266950	A1	9/2014	Cicero	

### OTHER PUBLICATIONS

PCT Search Report and Written Opinion of the ISA for PCT/US2016/026099 dated Nov. 17, 2016; 10 Pages.

### \* cited by examiner

Primary Examiner — Hoang V Nguyen (74) Attorney, Agent, or Firm — Daly, Crowley, Mofford & Durkee, LLP

### (57) ABSTRACT

Methods and apparatus for a directive, instantaneous wide bandwidth antenna including a ground plane having a recess with a tapered region accessible by an electromagnetic field via a radiating aperture at a forward end of the recess. The dielectric feed can have a tapered portion proximate the tapered region to guide the electromagnetic field into the recess through the radiating aperture and influence pattern directivity. The antenna can further include a conductive plating disposed at least partially about the dielectric feed in a wedge configuration to influence pattern beam width. The dielectric feed can include a conductive portion on a bottom of the wedge coupled to the conductive plating and to a grooved trace.

### 20 Claims, 11 Drawing Sheets

